

# Product data sheet


TRAFFIK LED 68W 10150LM 4000K IP66 O46 - FOR EXPRESS ROADS GRAY II  
130292.3L122.060

LUG



Professional streetlight luminaire for LED light sources. Mounting: on outriggers  $\varnothing 60/48\text{mm}$  Body: high pressure die-cast aluminum Lateral Surface Wind Exposed:  $0.033\text{ m}^2$ . Power: 220-240V 50/60Hz Available on request: DIM 1..10V, LLOC, twilight sensor, 10kV surge protection, NTC Other remarks: the pole and boom are not part of the luminaire; luminaire available in protection class I and II Warranty: 5 years Application: local roads, express roads, town roads, residential area roads, area lighting, avenues, promenade, parking areas Type of optics: O46 - for express roads

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	68 W	CRI	70
Total flux	10150 lm	LOR	100%
Luminous efficacy	149 lm/W	Total power	68 W

## Mounting mode

Pole top mounted

## Shape and measurements

Length: 19.88 in

Width: 9.06 in

Height: 3.15 in

## Adjustability

Fixed

## Design

Color of housing: Silver gray

## Electric

System power: 68 W

Controller: DALI

Appliance Class: II

## Protection

IP: 66

IK: 08