



Product data sheet

STANDARD
50500.889.1
RZB



Series: Standard Type of Protection: IP 44 Protection Class: II Voltage: - 250 / 0 - 60 Hz Base: plastic, grey. Five cable inlets, one cable inlet with cable grommet. Cover: textured glass, transparent. Protective cage: steel wire, "galvanised; screw mounting." Available Colours: grey Type of Installation: Ceiling mounting, Wall (surface) Dimensions: L 176, B 122, H 110 Lamp: 1 x E27 max. 60 W Socket 1: E27 Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK07 (2 Joule) Beam Angle: 90°/90°/62°/90° Unified Glare Ratio: 26,1 EEC: A++ - E

Light output 1



1 x Halogen low voltage lamp without reflector

Nominal lamp power	46 W	Socket	E27
Lamp flux	700 lm	LOR	72%
Luminous efficacy	12 lm/W	ULOR	17%
CCT	3000 K	Total flux	501 lm
CRI	90	Total power	42 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 4.80 in
Width: 6.93 in
Height: 4.33 in

Adjustability

Fixed

Electric

System power: 42 W

Protection

IP: 44
IK: 07