

Product data sheet

OUTDOOR LIGHTING
V1-S1-00648-40Y34-6603050 LEVANTE PLAZA 30W 5000K ZHAGA
VARTON




IP
66

IK
03

LED street light luminaire with a concise design. Adjustable spigot. Cast aluminum housing. Application: parking, squares and parks. Installation: pole mounted and side-entry mounted (Ø40mm-48mm/Ø48mm-60mm). Power factor: 0,95 Ingress protection (IP): IP66 Impact resistance: IK03 Protection class: I AC frequency, Hz: 50 Flicker, %: 5 Climatic modification and category of placement: YXJ11 Color rendering index: 70-79 Nominal voltage, V: 220...230 <https://www.varton.ru/products/ulichnoe-osveshchenie/levante/levante-plaza-dlya-ploshchadi/svetodiodnyy-svetilnik-varton-ulichnyy-levante-plaza-30-vt-kronshteyn-48-mm-5000-k-ral9003-belyy-mua/>

Light output 1



1 x LED			
Nominal lamp power	30 W	LOR	100%
Lamp flux	4500 lm	Total flux	4500 lm
Luminous efficacy	150 lm/W	Total power	30 W
CCT	5000 K		
CRI	70		

Mounting mode

Pole integrated

Shape and measurements

Length: 23.46 in

Width: 5.35 in

Height: 3.98 in

Adjustability

Fixed

Electric

System power: 30 W

Protection

IP: 66

IK: 03