


Product data sheet

CRUISER 2 PLUS LED DALI 22600LM 4000K TEMPERED GLASS IP66 110° GRAY
090342.3L04.013
LUG



Industrial luminaire for LED light sources. Mounting: surface mounted, in the ceiling, with mounting frame (sold separately), suspended, on chains (on request), for hanging on a cable, with special mounting bracket (on request) Body: high pressure die-cast aluminum Power: 220-240V 50/60Hz Lifetime (L80B10): 100 000 h Additional information: Ball impact resistance. The possibility of using one or more power supplies in the luminaire. Warranty: 5 years Application: warehouses, logistics centers, industrial facilities, sport facilities, roofing, outdoor installation without roof on special request (index extension: .985) Type of optics: lens

Light output 1 (integrated)



Lamp type	LED	CCT	4200 K
Nominal lamp power	204 W	CRI	80
Total flux	22600 lm	LOR	100%
Luminous efficacy	111 lm/W	Total power	204 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 26.57 in
Width: 15.67 in
Height: 3.54 in

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 204 W
Controller: DALI
Appliance Class: I

Protection

IP: 66
IK: 09
Resistant to impact of balls