Product data sheet


ECLDISPLAY_WHITE
ECLDISPLAYCCFC_WHITE_PROFILE1020_MAX ZOOM
PROLIGHTS



IP 20 IK 08

EclDisplay is a range of revolutionary and flexible LED spotlights designed for galleries, retail and any public venue where an advanced but classical looking fixture is needed, with several control options, sources and optic versions available to precisely meet any application. The EclDisplay CCFC is the version of the EclDisplay range made to be connected to an external Constant Current PSU and driver (max 4 x 1.4A/4.5V), selecting among the PROLIGHTS accessories or any third-party compatible component, leaving to System Integrators to install this luminaire in venues with their own wiring distribution and control. EclDisplay CCFC includes a high-efficiency 40W RGB + Warm White LED capable of delivering both a Full Colour spectrum and also tuneable White, and it is completed with a wide selection of optional zoomable profile or wash lenses, and other optical accessories like louvres and snoots, making it a truly a multi-purpose fixture. Features: Constant Current version to be connected to external PSU and driver (max 4 x 1.4A/4.5V) 40W RGB + Warm White LED capable to deliver both a Full Colour generation and also Tunable White Multiple lens options: zoomable profile or wash optics

Light output 1



1 x LED

Nominal lamp power	18.1 W	LOR	100%
Lamp flux	245 lm	Total flux	245 lm
Luminous efficacy	14 lm/W	Total power	18.1 W
CCT	3382 K		
CRI	77		

Mounting mode

Ceiling mounted, Contact rail, Standing / Bollard

Shape and measurements

Length: 39.37 in
Width: 39.37 in
Height: 39.37 in

Adjustability

Rotatable, Tiltable, Free

Electric

System power: 18.1 W
Controller: DMX, DALI
Color adjustable
Appliance Class: I

Protection

IP: 20
IK: 08
Surface temperature: 65°C
Designation labels: CE