Product data sheet


X-LINE SLIGHT UP&DOWN LED 5500/6600 PLX-T/MICRO-PRM E 34 830 LINE-S / L-1689MM S-1,5M
19.4427.3811.34
LUXIONA



IP 40 IK 04

Indoor luminaire. Assembly: surface mounted on slings. The body material is aluminum. Colour - RAL 9016 (white). Dimensions: 1689 x 34 x 68 mm. Diffuser: PLX-T/Micro-PRM (transparent PMMA/micro-prismatic diffuser PMMA) [up/down]. The efficiency of the optical system is 78,81%. Beam angle: (C0-C180) / (C90-C270) - 86,2° / 111°. Light source type: LED. Colour of the light 3000 K. SDCM=3. CRI>80. Lifetime of LED sources: 80000 h L80/B10. Luminaire luminous flux: 9734,1 lm. Power of luminaire: 71,3 W. Luminaire's light efficiency: 136,5 lm/W. Driver: standard on/off (E). Voltage 220..240 V, 50..60 Hz. Power factor cosφ: >0,95. Circuit load capacity: 8 (B10), 13 (B16), 11 (C10), 18 (C16). Operating temperature range: 5 ÷ 35° C. Protection degree: IP40. Impact resistant: IK04. Protection against electric shock: I. Photobiological risk class (IEC/EN 62471): RG0.

Light output 1



1 x LED

Nominal lamp power	71.3 W	LOR	52%
Lamp flux	12244 lm	Total flux	6420 lm
Luminous efficacy	172 lm/W	Total power	71.3 W
CCT	3000 K		
CRI	80		

Mounting mode

Pendant

Shape and measurements

Length: 66.50 in
Width: 1.34 in
Height: 2.68 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 71.3 W
Appliance Class: I

Protection

IP: 40
IK: 04

Other operating numbers

Ambient temperature range: 41...95°F