


# Product data sheet

ALPHABET FOCUS RECESSED LUMINAIRE, LENS WALLWASHER  
AF1105108-33-40\_36W  
SCHMITZ | WILA



alphabet focus LED 4000 K Recessed Luminaire, Light distribution direct, asymmetric Wallwasher Lens Wallwasher Product: AF1105108-33-40 Operating technology: independent driver required Lens wall washer create a uniform illumination on vertical surfaces without any hard shadow. Room proportions can be perfectly emphasized thanks to a harmonious brightness distribution. Light Technique asymmetric light distribution highly precise optical system, combining primary focus lens and secondary light control lens CRI > 90 constant colour temperature 4000K chromaticity stability with <3SDCM lifetime 50.000 h (L70) aluminium reflector (Al99.98), high-polished Luminaire housing stable housing design, made of aluminium die-cast and UV resistant plastics minimised ring thickness of only 2mm for homogeneous appearance in the ceiling ring colour white, RAL9016 Operating and assembly technology Order LED gear box separately Gear boxes suitable for connection to central battery systems Quick installation due to 4-point screw fixing Suitable for ceiling thicknesses of 12-25 mm (1-12 mm by using optional extension kit, Art.-No. 89081) Reflector with safety suspension Lamp Wattage: 36 W Colour Rendering Index: 90 Colour Temperature: 4000 K Luminaire Luminous Flux: 1980 Llm System Efficiency: 51 Llm/W Number Luminaires LZ: 0.07 Connector: Screw Connector, 3 x 1.5 mm2 Reflector Size: R15 Diameter D: 172 mm Cut-out CO: 165 mm Overhang OH: 145 mm Installation Depth RD: 200 mm Total Weight: 1.7 kg Degree of Protection IP20 CE-Sign Total system: Protection class 2 Data record AF1105108-33-40\_36W

## Light output 1



### 1 x General service incandescent lamp

|                    |         |             |         |
|--------------------|---------|-------------|---------|
| Nominal lamp power | 39 W    | LOR         | 100%    |
| Lamp flux          | 1980 lm | Total flux  | 1980 lm |
| Luminous efficacy  | 51 lm/W | Total power | 39 W    |
| CCT                | 4000 K  |             |         |
| CRI                | 90      |             |         |

## Mounting mode

Ceiling recessed

## Shape and measurements

Height: 7.87 in  
Diameter: 6.77 in

## Adjustability

Fixed

## Design

Color of housing: White

## Electric

System power: 39 W  
Appliance Class: II

## Protection

IP: 20