

# Product data sheet


VIVITA DECOR RING WITH SHADE LL 830 SYM CLO CL2 CG  
305086-565  
FAGERHULT



IP  
66

Installation Luminaire for assembly on a post, with post top Ø 60 mm. Connection Supplied with 5 m 2x1,5 mm<sup>2</sup> connection cable (H05RN-F). Design Body, heat sink and cover in cast aluminium. Diffuser of impact resistant UV-stabilised polycarbonate. Ballast integrated in the luminaire. Louvre Decor rings in acrylic (PMMA). Reflector Symmetrical reflector in acrylic (PMMA) or asymmetrical reflector in sheet metal. Light Distribution Symmetrical or asymmetrical. Dimming CLO (Constant Light Output) maintains the correct light from the luminaire for the duration of its service life. Night-time dimming 2, dims down for eight hours. Other options for light control available on request. Standard Colour Alu-grey (RAL 9006). LED-information Driver with integrated surge protection (DM: 6 kV.)

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	22 W	CRI	80
Total flux	1964 lm	LOR	100%
Luminous efficacy	89 lm/W	ULOR	8%
		Total power	22 W

## Mounting mode

Pole top mounted

## Electric

System power: 22 W

## Shape and measurements

Length: 28.17 in  
Width: 28.35 in  
Height: 21.38 in

## Protection

IP: 66

## Adjustability

Fixed

## Design

Color of housing: Silver gray