


Product data sheet

SUP2 L LED400-940 SSP DIM 3CV WH
60714954
ZUMTOBEL



LED spotlight module with one LED spotlight head, "maxi" construction size; equipped with lens system for high quality accent lighting in museums and exhibitions spaces; combination of LED PCBs, lens and film creates uniform light distribution with high intensity and soft transitions, without stray light from the light cone; Luminaire with 3-phase universal adapter with control gear unit in trackbox adapter (only for Zumtobel 3-phase/L3+DALI track); lamp(s): 1/14.5W, Colour rendering Ra > 90, colour temperature 4000 K; Luminaire or spotlight with SUPERSPOT distribution; colour tolerance: SDCM 2 initial, LED PCBs premium-selected; Luminaire luminous flux: 375 lm, Luminaire efficacy: 26 lm/W; service life: 50000h for luminous flux at 90% of initial value; dimming of illuminance, Luminaire with dimming directly over luminaire; flicker-free light (amplitude dimming); lamp unit can rotate through 360° and tilt through 90°; axes of movement fixed independently using Allen key; lamp unit of die-cast aluminium, coated white; optic consists of glass lens and film of plastic; front ring is for glare reduction and accommodating films; total power: 14.5 W; mains voltage: 220-240V/ 50/60Hz; dimensions: 150x65x157 mm; weight: 0.66 kg; Note: horizontal and vertical wall mounting is permissible; not suitable for point outlets; film can be replaced to achieve other light distribution patterns; ring louvre or the extended anti-glare cylinder can be exchanged for the front ring.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	14.5 W	CRI	90
Total flux	375 lm	LOR	100%
Luminous efficacy	26 lm/W	Total power	14.5 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 5.91 in
Width: 2.56 in
Height: 6.18 in
Weight: 0.7 kg

Design

Material impression: Aluminum
Color of housing: White

Electric

System power: 14.5 W
Voltage: 220-240 V AC
Appliance Class: I

Protection

IP: 20
Designation labels: CE