


Product data sheet

DAMP-PROOF DIFFUSER LUMINAIRE SPLASH 2 27.2- 47.4W ML7300/6310/5350/4310LM 7300LM CRI > 80 4000K ON
2011.9474 - SPLA2 1450 LED7300-840-ML NB PC ONF E3H
REGENT



Damp-proof diffuser luminaire Splash 2 for surface, wall, pendant mounting and mounting rail, with LED, 27.2 -, system power: 47.4 W, ML7300/6310/5350/4310 lm, luminous flux of luminaire 7300 lm, colour rendering index CRI > 80, colour temperature 4000 K, neutral white, colour tolerances SDCM 3, lifetime LED L90 50'000 h, photobiological safety: the luminaire poses no danger (RG0), 230 V, nominal current: 0.206 A, direct light emission, concentrated beam, 1 integral control gear, ON/OFF, with emergency unit, for non-maintained and maintained mode, with self-test, complete with battery pack, (burning life 3h), housing in polycarbonate (PC) light grey and diffuser in polycarbonate (PC), transparent, with chrome steel clamps, protection class I, ingress protection IP66 / IP69, glow wire test 850 °C, impact strength: IK 10, for ambient temperatures 0 to +40 °C, this product contains a light source of energy efficiency class C and EPREL registration number: 2258935 L = 1450 mm, B = 98 mm, H = 84 mm,

Light output 1



1 x LED			
Nominal lamp power	34.2 W	LOR	100%
Lamp flux	7300 lm	ULOR	10%
Luminous efficacy	213 lm/W	Total flux	7301 lm
CCT	4000 K	Total power	47.4 W
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 57.09 in
Width: 3.90 in
Height: 3.62 in
Weight: 2.1 kg

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 47.4 W
Appliance Class: I

Protection

IP: 68
IK: 10