

Product data sheet

COLOUR
501004.003
RZB




IP
44

IK
07

Series: Colour Type of Protection: IP 44 Protection Class: II Voltage: - 250 / 0 - 60 Hz Base and protective cage: plastic. Two cable inlets. Cover: textured glass, transparent. Protective cage fastening with screws. Available Colours: jet black (RAL 9005) Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 200, H 100 Lamp: 1 x E27 max. 100 W Socket 1: E27 Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK07 (2 Joule) Beam Angle: 171°/122° Unified Glare Ratio: 19,3 EEC: A++ - E

Light output 1



1 x Compact fluorescent lamp

Nominal lamp power	15 W	Socket	E27
Lamp flux	970 lm	LOR	50%
Luminous efficacy	32 lm/W	ULOR	8%
CCT	2700 K	Total flux	486 lm
CRI	80	Total power	15 W

Mounting mode

Wall mounted

Shape and measurements

Height: 6.30 in
Diameter: 7.87 in

Adjustability

Fixed

Design

Color of housing: Black

Electric

System power: 15 W

Protection

IP: 44
IK: 07