


Product data sheet

GUIDELED SL 13091.1 CG-S RECESSED

40071354484


EATON EMERGENCY LIGHTING



IP
41


GuideLed SL 13091.1 CG-S, round recessed mounting luminaire, with asymmetric optics for exit route lighting with 1 lx for mounting heights up to 15 m and for higher illuminance levels, e.g. 10.8 lx acc. NFPA, LED-Supply and CG-S technology (20 addresses) in a plastic housing with strain relief

Light output 1 (integrated, emergency)



Lamp type	LED	CCT	6500 K
Nominal lamp power	3.9 W	CRI	80
Total flux	250 lm	LOR	100%
Luminous efficacy	64 lm/W	Total power	3.9 W

Light output 2 (integrated)



Lamp type	LED	CCT	6500 K
Nominal lamp power	3.9 W	CRI	80
Total flux	250 lm	LOR	100%
Luminous efficacy	64 lm/W	Total power	3.9 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 16.54 in

Width: 16.54 in

Height: 13.78 in

Adjustability

Fixed

Electric

System power: 7.8 W

Information regarding emergency functions

Supplementary emergency lighting

Emergency sign: N/A

Protection

IP: 41

Design

Designer: Ruben Saldaña