
Product data sheet

BOX_AS_424_LED_53W_NEUTRAL_L1010MM
8215023_
PETRIDIS



Box combines stringent basic geometry with perfect contemporary style. Uniformly illuminated, without annoying reflections, it gives a strong architectural identity to various working areas (offices, stores, houses etc). It is available in five dimensions: 300, 400, 620, 920 and 1200mm and it can be combined with QR111 module. Technical Features - Aluminium body, painted electrostatically in selected colour. - Aluminium spot base, painted electrostatically in selected colour. - Opal plexi glass cover. - Connection for operation at 12V with electronic transformer (lamp QR111). - Pure light without IR/UV radiation. - Efficient thermal management. - Operation life: 50,000 hours with efficiency > 80% of the initial luminous flux (L80B10). - Connection for operation on 230V-50/60Hz. Upon Request - Connection for emergency lighting system, for one or three hours.

Light output 1



1 x LED

Nominal lamp power	53 W	LOR	50%
Lamp flux	7700 lm	Total flux	3826 lm
Luminous efficacy	145 lm/W	Total power	53 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 39.76 in
Width: 13.78 in
Height: 3.94 in

Adjustability

Fixed

Design

Material impression: Aluminum, Plastic

Electric

System power: 53 W
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 40
Designation labels: CE