


Product data sheet

O65-1550 LED 600 OP
GLAMOX



Light source LED 120-1200 830/840 Body material & colour The body is made of extruded clear or opal UV-resistant polycarbonate. End caps in anodized aluminium and fixed end brackets in polycarbonate. Mounting Installation directly on the ceiling or wall with integrated fixed end brackets. Accessories 24Vdc remote power supply. Supply cable with single connector. Supply cable with double connector for row mounting. IP68 terminal blocks. Connection Integrated quick connectors in the end caps. Installation requires connection cables for power supply and row mounting. Maximum total length for row mounting exclusive cables is 5 meters. Cables must be ordered separately. Optics Diffuse (OP). Clear (CL). Power supply 24Vdc remote power supply for fixed output or dimming (1-10V/SwitchDim). Power supply must be ordered separately.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	15 W	CRI	80
Total flux	598 lm	LOR	100%
Luminous efficacy	40 lm/W	ULOR	50%
		Total power	15 W

Mounting mode

Wall mounted

Shape and measurements

Height: 0.98 in

Diameter: 61.18 in

Adjustability

Fixed

Electric

System power: 15 W

Appliance Class: III

Protection

IP: 65

IK: 06