



Product data sheet

LEEDS 3 SURFACE FACADE LUMINAIRES
LEE-30041-M-M-8040
LIGMAN




- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 2700K,3000K and 4000K - Die-cast aluminium housing and frame - Pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Stainless steel fasteners in grade 304 with zinc flake coating (ZFC) - Durable silicone rubber gasket - Clear toughened glass - High-efficiency PMMA lens - Integral control gear - Optional surface mounting box for easy wiring or conduit connection when wiring from behind is not possible

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	13.4 W	CRI	80
Total flux	1655 lm	LOR	100%
Luminous efficacy	124 lm/W	Total power	13.4 W

Light output 2 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	13.4 W	CRI	80
Total flux	1655 lm	LOR	100%
Luminous efficacy	124 lm/W	Total power	13.4 W

Mounting mode

Wall recessed

Shape and measurements

Length: 3.15 in
Width: 7.87 in
Height: 3.74 in
Weight: 1.5 kg

Adjustability

Fixed

Electric

System power: 26.8 W
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 65
IK: 07
Surface temperature: 40°C