# Product data sheet

LINA60-S 04S-200F-30GDE/930, W
04S-200F-30GDE/930
HALLA



IP 20

04S-200F-30GDE/930, W Luminaire recessed/surface/suspended Material of luminaire: Colour of luminaire: Shape of luminaire: Linear Size: 561 x 57 x 67 mm Type of installation: Recessed, Surface, Suspended Distribution: Direct Optics type: Reflector Protection class: I Voltage: 220-240V

## Light output 1 (integrated)



| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 3000 K |
| Nominal lamp power | 13.6 W | CRI | 80 |
| Total flux | 1200 lm | LOR | 100% |
| Luminous efficacy | 88 lm/W | Total power | 13.6 W |

## Light output 2 (integrated)



| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 3000 K |
| Nominal lamp power | 13.6 W | CRI | 80 |
| Total flux | 1200 lm | LOR | 100% |
| Luminous efficacy | 88 lm/W | Total power | 13.6 W |

## Light output 3 (integrated)



| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 3000 K |
| Nominal lamp power | 13.6 W | CRI | 80 |
| Total flux | 1200 lm | LOR | 100% |
| Luminous efficacy | 88 lm/W | Total power | 13.6 W |

### Mounting mode

Ceiling mounted, Pendant

### Shape and measurements

Height: 6.30 in

Diameter: 2.17 in

### Adjustability

Rotatable, Tiltable

### Electric

System power: 40.8 W

Appliance Class: I

### Protection

IP: 20