# Product data sheet

WALL MOUNTED LUMIN. VILLAGE 300 - SUSPENDED 2700K 13.19520.1VXXX

HESS









Round luminaire canopy made of aluminium. Cylindrical luminaire enclosure made of PMMA, satin look in the upper part. Encased by two-part aluminium holding rods and five design rings made of aluminium. Wall bracket made of steel, galvanised.


# Light output 1



1 x LED			
Nominal lamp power	53 W	LOR	100%
Lamp flux	3961 lm	ULOR	100%
Luminous efficacy	75 lm/W	Total flux	3961 lm
CCT	2700 K	Total power	53 W
CRI	80		



1 x LED			
Nominal lamp power	27 W	LOR	100%
Lamp flux	2113 lm	ULOR	100%
Luminous efficacy	78 lm/W	Total flux	2113 lm
CCT	2700 K	Total power	27 W
CRI	80		



1 x LED			
Nominal lamp power	27 W	LOR	100%
Lamp flux	3000 lm	ULOR	100%
Luminous efficacy	111 lm/W	Total flux	3000 lm
CCT	2700 K	Total power	27 W
CRI	80		

1 x LED  Nominal lamp power  Lamp flux  Luminous efficacy  CCT  CRI	27 W 2135 lm 79 lm/W 2700 K 80	LOR ULOR Total flux Total power	100% 100% 2135 lm 27 W
1 x LED  Nominal lamp power  Lamp flux  Luminous efficacy  CCT  CRI	27 W 3084 lm 114 lm/W 2700 K 80	LOR ULOR Total flux Total power	100% 100% 3084 lm 27 W
1 x LED  Nominal lamp power  Lamp flux  Luminous efficacy  CCT  CRI	27 W 2075 lm 77 lm/W 2700 K 80	LOR ULOR Total flux Total power	100% 100% 2075 lm 27 W
1 x LED  Nominal lamp power  Lamp flux  Luminous efficacy  CCT  CRI	37 W 2940 lm 79 lm/W 2700 K 80	LOR ULOR Total flux Total power	100% 100% 2940 lm 37 W
1 x LED  Nominal lamp power  Lamp flux  Luminous efficacy  CCT	37 W 4287 lm 116 lm/W 2700 K	LOR ULOR Total flux Total power	100% 100% 4287 lm 37 W

80


CRI

1 x LED  Nominal lamp power  Lamp flux  Luminous efficacy  CCT  CRI	37 W 2972 lm 80 lm/W 2700 K 80	LOR ULOR Total flux Total power	100% 100% 2972 lm 37 W
1 x LED  Nominal lamp power  Lamp flux  Luminous efficacy  CCT  CRI	37 W 4405 lm 119 lm/W 2700 K 80	LOR ULOR Total flux Total power	100% 100% 4405 lm 37 W
1 x LED  Nominal lamp power  Lamp flux  Luminous efficacy  CCT  CRI	37 W 2889 lm 78 lm/W 2700 K 80	LOR ULOR Total flux Total power	100% 100% 2889 lm 37 W
1 x LED  Nominal lamp power  Lamp flux  Luminous efficacy  CCT  CRI	53 W 5698 lm 108 lm/W 2700 K 80	LOR ULOR Total flux Total power	100% 100% 5698 lm 53 W
1 x LED  Nominal lamp power  Lamp flux  Luminous efficacy  CCT	27 W 1962 lm 73 lm/W 2700 K	LOR ULOR Total flux Total power	100% 100% 1962 lm 27 W

80


CRI

7478W87+1	1 x LED			
	Nominal lamp power	53 W	LOR	100%
	Lamp flux	5702 lm	ULOR	100%
	Luminous efficacy	108 lm/W	Total flux	5702 lm
XXTTXX	CCT	2700 K	Total power	53 W
	CRI	80		
XXXX				
XXX				
7-7-2011	1 x LED			
	Nominal lamp power	53 W	LOR	100%
	Lamp flux	4032 lm	ULOR	100%
	Luminous efficacy	76 lm/W	Total flux	4032 lm
XXXXXX	CCT	2700 K	Total power	53 W
	CRI	80		
XX				
XXXX				
7478/1/847+	1 x LED			
	Nominal lamp power	53 W	LOR	100%
	Lamp flux	4075 lm	ULOR	100%
	Luminous efficacy	77 lm/W	Total flux	4075 lm
XXXXXX	CCT	2700 K	Total power	53 W
	CRI	80		
XXXX				
XXXX				
74-78-14-1	1 x LED			
	Nominal lamp power	53 W	LOR	100%
The state of the s	Lamp flux	5859 lm	ULOR	100%
	Luminous efficacy	111 lm/W	Total flux	5859 lm
XXX	CCT	2700 K	Total power	53 W
	CRI	80		
XXXX				
74-45-47	1 x LED			
	Nominal lamp power	53 W	LOR	100%
	Lamp flux	3745 lm	ULOR	100%
	Luminous efficacy	71 lm/W	Total flux	3745 lm
XXXIIXX	CCT	2700 K	Total power	53 W
	CRI	80		





Nominal lamp power	37 W	LOR	100%
Lamp flux	2730 lm	ULOR	100%
Luminous efficacy	74 lm/W	Total flux	2730 lm
CCT	2700 K	Total power	37 W
CRI	80		



#### 1 x LED

Nominal lamp power	37 W	LOR	100%
Lamp flux	4285 lm	ULOR	100%
Luminous efficacy	116 lm/W	Total flux	4285 lm
CCT	2700 K	Total power	37 W
CRI	80		

Mounting mode

Wall mounted

# Shape and measurements

Length: 48.07 in Width: 14.72 in Height: 28.68 in

# Adjustability

Fixed

Electric

System power: 27-53 W

Protection

IP: 65