


Product data sheet

PACIFIC LED GEN5 WT490C SIA EL3 L1200 1 XLED80S/840 VWB
8670882
PHILIPS



Robust, connectable luminaire with outstanding performance. Pacific LED gen5 is an innovative and best-in-class LED waterproof luminaire that is praised for its optimal performance. It meets the demanding requirements of contemporary and harsh industries. It is a very robust, compact and reliable luminaire with excellent quality of light. With a high degree of mechanical (IK08), water and dust protection (IP66), combined with proven chemical resistance, the Pacific LED gen5 can perfectly withstand the harsh conditions of the automotive, food and heavy industries. But it also performs well in parking garages and warehouses. Pacific LED gen5 luminaires provide superior, artefact-free light quality and homogeneous light, offered with multiple optics and broad range of light outputs (up to 15,000 lm). This ensures more flexibility in optimized light scheme planning. They are also designed with a circular approach, which means these fully-serviceable luminaires can be upgraded to extend their overall lifecycle. The luminaires stand out because of their quick and easy installation that facilitates through wiring and various connection and mounting options. But also, because of their attractive TCO, energy efficiency, and ease of maintenance – with minimum of disruption to operations in demanding applications. To make the Pacific LED gen5 even more complete, system integration with Interact Industry opens up additional opportunities for optimized efficiency, energy savings, improved light management, productivity, and safety. Making it future proof in every aspect. Discover Pacific LED gen5. Optimal performance for demanding environments.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	3 W	CRI	80
Total flux	500 lm	LOR	100%
Luminous efficacy	167 lm/W	ULOR	3%
		Total power	3 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 48.03 in
Width: 3.78 in
Height: 2.68 in

Electric

System power: 3 W

Protection

IP: 66
IK: 08