Product data sheet

SMART KUP 160 IP55 LED GE 3000K MEDIUM BLACK STRUC 13024432

MODULAR









Subtle lighting Smart kup is one of the 3 forms of the Smart family. The cone of the Smart kup ends in a fine trim. A trim particular Modular. The same subtle trim is used in several other Modular luminaires. The Smart family's styling is based on our most popular designs. Concretely this means that the luminaires consist of a light source (LED or halogen) which can be combined with one of three trims to suit your needs. The new spotlights can be combined with Smart mask, Smart surface box or surface tubed to form the perfect solution for any interior. Choose a white, black or gold finishing. Also available in different sizes, fix and adjustable, IP version, ...

Light output 1




| I x LED | |
|--------------------|---------|
| Nominal lamp power | 36.3 W |
| Lamp flux | 4095 lm |
| Luminous efficacy | 99 lm/W |
| CCT | 3000 K |
| CRI | 90 |
| | |

| LOR | 88% |
|-------------|---------|
| Total flux | 3609 lm |
| Total power | 36.3 W |
| | |
| | |




| 1 x LED | |
|--------------------|----------|
| Nominal lamp power | 30.8 W |
| Lamp flux | 3541 lm |
| Luminous efficacy | 101 lm/W |
| CCT | 3000 K |
| CRI | 90 |

| LOR | 88% |
|-------------|---------|
| Total flux | 3121 lm |
| Total power | 30.8 W |
| | |
| | |




| 1 x LED | | | |
|--------------------|----------|-------------|---------|
| Nominal lamp power | 23.5 W | LOR | 88% |
| Lamp flux | 2853 lm | Total flux | 2514 lm |
| Luminous efficacy | 107 lm/W | Total power | 23.5 W |
| CCT | 3000 K | | |
| CRI | 90 | | |
| | | | |





2095 lm 115 lm/W 3000 K 90 LOR Total flux 88% 1846 lm

Total power 16 W



1 x LED

Lamp flux

CCT

CRI

Luminous efficacy

Nominal lamp power 49.7 W
Lamp flux 5296 lm
Luminous efficacy 94 lm/W
CCT 3000 K
CRI 90


LOR Total flux

Total power

Total power

88% 4667 lm

49.7 W



1 x LED

Nominal lamp power 42 W
Lamp flux 4600 lm
Luminous efficacy 97 lm/W
CCT 3000 K
CRI 90

LOR 88% Total flux 4054 lm

42 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 6.30 in Width: 6.30 in Height: 5.08 in Weight: 0.91 kg

Adjustability

Fixed

Electric

System power: 16-49.7 W Appliance Class: II

Protection

IP: 55