

Product data sheet

TRIONA ROUND P
312386.002.730
RZB




IP
20

IK
03

Series: TRIONA round Decorative round LED pendant-mounted surface luminaire. Flat, seamless frame: aluminium extrusion profile, powder coated. Cover made of sheet steel, powder-coated. Canopy made of aluminium, powder-coated. Direct light emission through a diffuser plastic opal. Indirect light emission through a flush diffuser made of satin-finish plastic. Lightguide and diffuser made of non-yellowing plastic (PMMA). Lateral light emission (RZB SIDELITE technology) for above-average homogeneous light distribution. Direct 70%, indirect 30% light emission. 3-point steel cable suspension, steplessly adjustable. Easy installation with transparent, adjustable pendant cable and canopy with magnetic fixing. Driver integrated. Colour: traffic white, matt (RAL 9016) Diameter: 681 mm Height: 52 mm Suspension length: 500-1200 mm Lamp: LED Socket: without socket Colour temperature: 3000K Colour rendering index (CRI): 80 System power: 94 W Rated luminous flux: 11300 lm Beam angle Down: 108° Luminous efficiency: 120 lm/W Control gear: Dimmable Bluetooth converter Protection class: I Type of protection: IP 20

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	94 W	CRI	80
Total flux	11300 lm	LOR	62%
Luminous efficacy	120 lm/W	ULOR	18%
		Total power	94 W

Mounting mode

Pendant

Shape and measurements

Height: 2.05 in
Diameter: 26.81 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 94 W

Protection

IP: 20
IK: 03