


Product data sheet

SAFESITE LED HIGH BAY 18250 LUMENS, WIDE DISTRIBUTION, DIFFUSED POLYCARBONATE LENS
HED5WC2CXXXXXN
DIALIGHT



SafeSite LED High Bay 18,250 Lumens 129 Watts 100-277V AC, 120-250V DC Cool White, 80CRI Diffused Polycarbonate Lens Class I Div 2 Groups A,B,C,D Class II Div 1 Groups E,F,G Class II Div 2 Groups F,G Class III Div 1&2 UL 844 (wet locations) CSA C22.2 No. 137-M81 NEMA 4X IK10 Wide Distribution IP66/67 Scaled IES File

Light output 1 (integrated)



Lamp type	LED	CCT	5181 K
Nominal lamp power	129 W	CRI	80
Total flux	18251 lm	LOR	100%
Luminous efficacy	141 lm/W	Total power	129 W

Mounting mode

Pendant

Shape and measurements

Length: 15.94 in
Width: 15.94 in
Height: 5.04 in

Adjustability

Rotatable, Tilttable

Electric

System power: 129 W
Voltage: 240 V AC, 120 V AC, 277 V AC, 110 V AC, 230 V AC
Appliance Class: I

Protection

IP: 66
IK: 10

Other operating numbers

Ambient temperature range: -40...149°F