

Product data sheet

OFFICE LUMINAIRES FOR SPECIAL CEILINGS
V1-A8-07080-100PD-4003540 35W 4000K OPAL DALI
VARTON




IP
40

IK
02

Input voltage (AC, 50Hz): 176...264 AC frequency: 50 Flicker: 1 Climatic modification and category of placement: YXЛ4 Height/depth: 35 Length: 600 Protection class: I Ingress protection (IP): IP40 Impact resistance: IK02 Width: 600 https://www.varton.ru/products/ofisnye-svetilniki-dlya-nestandardnykh-potolkov/varton-dlya-grand-line/grand-line-ip40-600x600/svetodiodnyy-svetilnik-var-ton-dlya-potolka-grand-line-35-vt-4000-k-600kh600-ip40-s-rasseivatelem-opa_2/

Light output 1



1 x LED			
Nominal lamp power	35 W	LOR	100%
Lamp flux	4480 lm	Total flux	4480 lm
Luminous efficacy	128 lm/W	Total power	35 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 23.62 in
Width: 23.62 in
Height: 1.38 in

Adjustability

Fixed

Electric

System power: 35 W

Protection

IP: 40
IK: 02