# Product data sheet


GRIFF S
GRIFF-S-CIR06-16LED-2700K-700 MA
RAGNI



IP 66

The Griff range is intended for small or medium height road or residential lighting for the Griff S luminaire and medium and large heights road lighting for the Griff L & XL luminaires. Elongated trapezoidal shaped, it has fins on the top exept for the L version going up to 64 LED. It is entirely made of injected cast aluminum and the dedicated PCB is protected by a screen-printed glass. The Griff XL can receive up to 80 LED. The thermal management of the luminaire is ensured by the module itself, thermally self-managed. Totally IP66, it is fixed laterally on a wall, a mast or a console or at the top of a mast. Griff S is available in 1 or 2 lights, Griff XL in 1 light only.

## Light output 1



1 x LED

| | | | |
|---|---|---|---|
| Nominal lamp power | 35.5 W | LOR | 100% |
| Lamp flux | 4653 lm | Total flux | 4653 lm |
| Luminous efficacy | 131 lm/W | Total power | 35.5 W |
| CCT | 2700 K | | |
| CRI | 70 | | |

### Mounting mode

Pole top mounted

### Shape and measurements

Length: 27.56 in
Width: 7.87 in
Height: 3.94 in

### Adjustability

Fixed

### Electric

System power: 35.5 W

### Protection

IP: 66