


Product data sheet

LIGHT LINEAR VT 2 BOLLARDS
VT-10011-T4-W40
LIGMAN




- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour Temperature 3000K ,4000K - Die-cast aluminium housing, frame and extruded aluminium column pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - One IP68 connector supplied with 0.2 m of 3x1.0 sqmm outdoor cable - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency PMMA lens - Clear toughened glass - Integral control gear

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	26.9 W	CRI	80
Total flux	2834 lm	LOR	100%
Luminous efficacy	105 lm/W	ULOR	18%
		Total power	26.9 W

Light output 2 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	26.9 W	CRI	80
Total flux	2834 lm	LOR	100%
Luminous efficacy	105 lm/W	ULOR	18%
		Total power	26.9 W

Mounting mode

Standing / Bollard

Shape and measurements

Length: 4.88 in
Width: 7.87 in
Height: 39.37 in
Weight: 9.9 kg

Adjustability

Fixed

Glare protection

Glare protection: UGR < 19

Electric

System power: 53.8 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Design

Color of housing: Black, White, Silver gray

Protection

IP: 65

IK: 07

Surface temperature: 40°C