Product data sheet


SCOOT 450 DELTA WHITE TW 2700-6500K CLO
54978
FAGERHULT



IP 20


Installation Two point suspension c/c 48 mm. Connection For permanent connection with 230 V; built-in LED driver. Snap-in terminal block 5x2.5 mm². 1-phase through-wiring possible. Surface mounted mains cable possible 180°. Design Luminaire body in plastic lacquered in various colours. Supplied with 3 m wire, 2,2 m transparent cable and white, plastic ceiling cup. Height adjustment is done on the luminaire using a friction lock. The ceiling cup handles inclined ceilings up to 20°. Louvre Opal - opal acrylic diffuser. Delta – microprism louvre in acrylic (PMMA). Light distribution Delta Ø 450 – Direct/indirect 65/35. Opal Ø 450 – Direkt/indirekt 70/30. Dimming DALI/phase-pulse control as standard. Tunable White and e-Sense Tune on request.

Light output 1




1 x LED

Nominal lamp power	35 W	LOR	100%
Lamp flux	2806 lm	ULOR	38%
Luminous efficacy	80 lm/W	Total flux	2806 lm
CCT	3000 K	Total power	35 W
CRI	90		



1 x LED

Nominal lamp power	35 W	LOR	100%
Lamp flux	2769 lm	ULOR	38%
Luminous efficacy	79 lm/W	Total flux	2769 lm
CCT	2700 K	Total power	35 W
CRI	90		



1 x LED

Nominal lamp power	35 W	LOR	100%
Lamp flux	3040 lm	ULOR	38%
Luminous efficacy	87 lm/W	Total flux	3040 lm
CCT	4000 K	Total power	35 W
CRI	90		

Mounting mode

Pendant

Shape and measurements

Length: 17.72 in

Width: 17.72 in

Height: 10.85 in

Adjustability

Fixed

Electric

System power: 35 W

Protection

IP: 20