


Product data sheet

CLOSE LED DIR-IND WHITE 1200 BETA OPTI 4K
12179
FAGERHULT



Installation Wire pendent. Installation via wire suspension requires wire brackets which provide flexible c/c, see accessories. Wire suspension, see accessories. Balanced. Connection Two Ø 19 mm cable entries fitted with blanking grommets on the top of the luminaire, see dimension chart. 3-way snap-in terminal block at each end. Luminaires for dimming, 5-way snap-in terminal block, 1-phase through-wiring possible. Design Luminaire body in sheet steel and end-caps of die-cast aluminium in a white (RAL 9016) structured or alu-grey (RAL 9006) structured finish. Louvre Beta Opti – double parabolic reflector louvre with satin matt metallised aluminium side and cross-blades with an integrated opal film that minimises the risk of uncomfortable glare from the diodes. Reflector The louvre acts as a reflector.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	54 W	CRI	80
Total flux	7166 lm	LOR	100%
Luminous efficacy	133 lm/W	ULOR	37%
		Total power	54 W

Mounting mode

Pendant

Shape and measurements

Length: 47.91 in

Width: 4.92 in

Height: 2.17 in

Adjustability

Fixed

Design

Color of housing: Silver gray, White

Electric

System power: 54 W

Protection

IP: 20