


Product data sheet

ATHLON AREA LIGHT / DOUBLE SIDED
7258-K-3-658-XX
UNILAMP




ATHLON is a series of mini floodlights with wide beam asymmetrical and bi-symmetrical light distribution. It operates with High Power LED module which is attached on aluminium body as a heat sink. The Alanod Miro reflectors used in this luminaire are designed by Photopia high-end lighting engineering software. The calibrated aiming unit provides accuracy of the light distribution on the illuminated surface. The range of accessories such as ground mount spike, tree strap and pole clamping unit makes it a dynamic floodlight choice. ATHLON is suitable to light up small to medium sized objects or areas such as signage boards, ceiling, building facades, etc.

Light output 1



1 x LED			
Nominal lamp power	25 W	LOR	95%
Lamp flux	3010 lm	Total flux	2847 lm
Luminous efficacy	120 lm/W	Total power	28 W
CCT	2700 K		
CRI	80		

Light output 2



1 x LED			
Nominal lamp power	25 W	LOR	95%
Lamp flux	3010 lm	Total flux	2847 lm
Luminous efficacy	120 lm/W	Total power	28 W
CCT	2700 K		
CRI	80		

Mounting mode

Pole top mounted, Pole integrated

Shape and measurements

Length: 9.67 in
Width: 4.13 in
Height: 9.23 in

Adjustability

Rotatable, Tilttable

Electric

System power: 56 W
Appliance Class: I

Protection

IP: 66
IK: 07