
## Product data sheet

ALPHABET SPECTRA RECESSED LUMINAIRE, DOWNLIGHT AS1102001-30-30 + 83819R08-WT\_11W


SCHMITZ | WILA





alphabet spectra LED 3000 K Recessed Luminaire, Light distribution direct Downlight Reflector white coated Product: AS1102001-30-30 Operating technology: independent driver required Lite Optic: 83819R08-WT Lite Optic Aluminium reflector, coated white Reflector with safety strap for easy installation Half-peak divergence  $\alpha = 60^{\circ}$  Light Technique CRI 98 (typ.), with R9≥90, R15≥95 highest colour consistency with 1x2 SDCM (initial), max. 3 SDCM covered by 5 years warranty constant colour temperature 3000 K lifetime 50.000 h (L80/B10); 50.000 h (L70/B0) covered by 5 years warranty Luminaire housing stable housing design, made of aluminium die-cast and UV resistant plastics minimised ring thickness of only 2 mm for homogeneous appearance in the ceiling ring colour white, RAL 9016 Operating and assembly technology LED driver to be ordered separately Driver suitable for connection to central battery systems Quick installation due to 2-point screw fixing Suitable for ceiling thicknesses of 12-25 mm (1-12 mm by using optional extension kit, Art.-No. 89081) Reflector with safety suspension Lamp Wattage: 11 W Colour Rendering Index: 98 Colour Temperature: 3000 K Luminaire Luminous Flux: 800 Llm System Efficiency: 67 Llm/W Halfpeak Divergence  $\alpha$ : 60° Number Luminaires LZ: 0.17 Connector: Screw Connector, 3 x 1.5 mm2 Reflector Size: R08 Diameter D: 102 mm Cutout CO: 95 mm Installation Depth RD: 95 mm Degree of Protection IP20 CE-Sign Total system: Protection class 2 Data record AS1102001-30-30+83819R08-WT\_11W

## Light output 1



CCT

CRI

## 1 x General service incandescent lampNominal lamp power12 WLamp flux800 lmTotal fluxLuminous efficacy67 lm/WTotal power

3000 K

98

LOR	100%
Total flux	800 lm
Total power	12 W

Mounting mode	Electric
Ceiling recessed	System power: 12 W
Shape and measurements	Appliance Class: II
Height: 3.74 in	Protection
Diameter: 4.02 in	IP: 20
Adjustability	
Fixed	

## Design

Color of housing: White