

Product data sheet


I-P65 LED O CG-S
IP65LED0230CG
EATON EMERGENCY LIGHTING



• LED escape sign luminaire with high protection class (IP65) for indoor and outdoor use • Robust construction made of polycarbonate with numerous knock-outs for cable entries (M20 - gland is not included in delivery) and double terminal for through-wiring • Low operating cost due to low power consumption • Minimum service requirement due to high service life of the LEDs (50,000 hours) • Shortened inspection effort due to CEWA GUARD technology • Automatic function monitoring of up to 20 luminaires per circuit • Reduced installation expenditures by STAR technology • Freely programmable mixed operation of the switching modes per luminaire in one circuit

Ordering details

Light output 1 (integrated, emergency)



Lamp type	LED	CCT	6000 K
Nominal lamp power	3.6 W	CRI	70
Total flux	112 lm	LOR	100%
Luminous efficacy	31 lm/W	Total power	3.6 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 19.69 in
Width: 5.59 in
Height: 2.17 in

Adjustability

Fixed

Electric

System power: 3.6 W
Suitable for feed-through wiring
Appliance Class: II

Information regarding emergency functions

Emergency lighting only
Emergency power supply: Central battery feed-in
Emergency sign: N/A

Protection

IP: 65
IK: 03