Product data sheet


LDSQ4B LED 4" SQUARE RECESSED DOWNLIGHT LDSQ4B30D010 EU4B30509727 4LBSQ1LI COOPER LIGHTING





Square new construction downlight or lensed wall wash, Excellent light control and low aperture brightness, Designed for standard or shallow plenums; ENERGY STAR® qualified, Square die-cast or spun aluminum reflectors, 6 color temperatures: 2400K, 2700K, 3000K, 3500K, 4000K and 5000K CCT, CRI: 80, 90 or 97; D2W[™] option from 3000K to 1850K, W2N Tunable White 2700K-6500K or 2000K-5000K, Lumens: 1,000-6,000; 0-10V dimming down to 1%, WaveLinx and DLVP connected lighting systems compatibility, Plaster lathing ring accessory offered for flush reflector transition

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	28 W	CRI	100
Total flux	1975 lm	LOR	100%
Luminous efficacy	71 lm/W	Total power	28 W

Mounting mode	Electric
Ceiling recessed	System power: 28 W
Shape and measurements	Protection
Length: 3.94 in	IP: 47
Width: 3.94 in	
Height: 3.94 in	

Adjustability

Fixed