Product data sheet


PML WITH BRACKET TOLEDO 660 - WITH LOUVRES DOUBLE ASY11 16LED 2200K
88.01200.0V002 + 10.31201.2V001
HESS



IP 54


Domed luminaire canopy, horizontally separated in two, made of aluminium, underside painted white. Support elements made of aluminium. Cylindrical luminaire enclosure made of PC. Round luminaire body made of aluminium with louvres. Bracket TOLEDO 660 double Made of galvanised steel Overhanging 450 mm on each side Spigot pole ø 76,1 mm

Light output 1




1 x LED

Nominal lamp power	15.7 W	LOR	100%
Lamp flux	1605 lm	ULOR	100%
Luminous efficacy	102 lm/W	Total flux	1605 lm
CCT	2200 K	Total power	15.7 W
CRI	80		




1 x LED

Nominal lamp power	11.1 W	LOR	100%
Lamp flux	1082 lm	ULOR	100%
Luminous efficacy	97 lm/W	Total flux	1082 lm
CCT	2200 K	Total power	11.1 W
CRI	80		




1 x LED

Nominal lamp power	33.9 W	LOR	100%
Lamp flux	3544 lm	ULOR	100%
Luminous efficacy	105 lm/W	Total flux	3544 lm
CCT	2200 K	Total power	33.9 W
CRI	80		




1 x LED

Nominal lamp power	31.6 W	LOR	100%
Lamp flux	3316 lm	ULOR	100%
Luminous efficacy	105 lm/W	Total flux	3316 lm
CCT	2200 K	Total power	31.6 W
CRI	80		




1 x LED

Nominal lamp power	29.4 W	LOR	100%
Lamp flux	3086 lm	ULOR	100%
Luminous efficacy	105 lm/W	Total flux	3086 lm
CCT	2200 K	Total power	29.4 W
CRI	80		




1 x LED

Nominal lamp power	27.1 W	LOR	100%
Lamp flux	2851 lm	ULOR	100%
Luminous efficacy	105 lm/W	Total flux	2851 lm
CCT	2200 K	Total power	27.1 W
CRI	80		




1 x LED

Nominal lamp power	24.8 W	LOR	100%
Lamp flux	2613 lm	ULOR	100%
Luminous efficacy	105 lm/W	Total flux	2613 lm
CCT	2200 K	Total power	24.8 W
CRI	80		




1 x LED

Nominal lamp power	22.5 W	LOR	100%
Lamp flux	2370 lm	ULOR	100%
Luminous efficacy	105 lm/W	Total flux	2370 lm
CCT	2200 K	Total power	22.5 W
CRI	80		




1 x LED

Nominal lamp power	20.2 W	LOR	100%
Lamp flux	2122 lm	ULOR	100%
Luminous efficacy	105 lm/W	Total flux	2122 lm
CCT	2200 K	Total power	20.2 W
CRI	80		



1 x LED


Nominal lamp power	18 W	LOR	100%
Lamp flux	1866 lm	ULOR	100%
Luminous efficacy	104 lm/W	Total flux	1866 lm
CCT	2200 K	Total power	18 W
CRI	80		



1 x LED


Nominal lamp power	13.4 W	LOR	100%
Lamp flux	1346 lm	ULOR	100%
Luminous efficacy	100 lm/W	Total flux	1346 lm
CCT	2200 K	Total power	13.4 W
CRI	80		

Light output 2




1 x LED

Nominal lamp power	31.6 W	LOR	100%
Lamp flux	3316 lm	ULOR	100%
Luminous efficacy	105 lm/W	Total flux	3316 lm
CCT	2200 K	Total power	31.6 W
CRI	80		




1 x LED

Nominal lamp power	29.4 W	LOR	100%
Lamp flux	3086 lm	ULOR	100%
Luminous efficacy	105 lm/W	Total flux	3086 lm
CCT	2200 K	Total power	29.4 W
CRI	80		




1 x LED

Nominal lamp power	27.1 W	LOR	100%
Lamp flux	2851 lm	ULOR	100%
Luminous efficacy	105 lm/W	Total flux	2851 lm
CCT	2200 K	Total power	27.1 W
CRI	80		




1 x LED

Nominal lamp power	24.8 W	LOR	100%
Lamp flux	2613 lm	ULOR	100%
Luminous efficacy	105 lm/W	Total flux	2613 lm
CCT	2200 K	Total power	24.8 W
CRI	80		




1 x LED

Nominal lamp power	22.5 W	LOR	100%
Lamp flux	2370 lm	ULOR	100%
Luminous efficacy	105 lm/W	Total flux	2370 lm
CCT	2200 K	Total power	22.5 W
CRI	80		




1 x LED

Nominal lamp power	20.2 W	LOR	100%
Lamp flux	2122 lm	ULOR	100%
Luminous efficacy	105 lm/W	Total flux	2122 lm
CCT	2200 K	Total power	20.2 W
CRI	80		




1 x LED

Nominal lamp power	18 W	LOR	100%
Lamp flux	1866 lm	ULOR	100%
Luminous efficacy	104 lm/W	Total flux	1866 lm
CCT	2200 K	Total power	18 W
CRI	80		




1 x LED

Nominal lamp power	15.7 W	LOR	100%
Lamp flux	1605 lm	ULOR	100%
Luminous efficacy	102 lm/W	Total flux	1605 lm
CCT	2200 K	Total power	15.7 W
CRI	80		




1 x LED

Nominal lamp power	13.4 W	LOR	100%
Lamp flux	1346 lm	ULOR	100%
Luminous efficacy	100 lm/W	Total flux	1346 lm
CCT	2200 K	Total power	13.4 W
CRI	80		



1 x LED

Nominal lamp power	11.1 W	LOR	100%
Lamp flux	1082 lm	ULOR	100%
Luminous efficacy	97 lm/W	Total flux	1082 lm
CCT	2200 K	Total power	11.1 W
CRI	80		



1 x LED

Nominal lamp power	33.9 W	LOR	100%
Lamp flux	3544 lm	ULOR	100%
Luminous efficacy	105 lm/W	Total flux	3544 lm
CCT	2200 K	Total power	33.9 W
CRI	80		

Mounting mode

Pole top mounted

Shape and measurements

Length: 38.43 in
Width: 3.74 in
Height: 12.91 in

Adjustability

Fixed

Electric

System power: 22.2-67.8 W

Protection

IP: 54