Product data sheet


BILLUND 2 STREET AND AREA LIGHTING LUMINAIRES
BIU-90053-T3-8040
LIGMAN



IP 66 IK 08

- Lamp LED - CRI Ra > 80 - Colour 3000K and 4000K - Die-cast aluminium housing - Pre-treated before powder coating ensuring high corrosion resistance - Thermal heat dissipation body - Single cable entry - One IP68 connector supplied with 0.3 m of 3x1.0 sqmm outdoor cable - Stainless steel fasteners in grade 304 with zinc flake coating (ZFC) - Durable silicone rubber gasket - Clear toughened glass - High-efficiency polycarbonate lens - Integral control gear - Surge protection 10kV - Constant lumen output (CLO) and Night-time dimming options

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	122 W	CRI	80
Total flux	13665 lm	LOR	100%
Luminous efficacy	112 lm/W	ULOR	50%
		Total power	122 W

Mounting mode

Pole integrated, Floor mounted

Shape and measurements

Length: 30.12 in
Width: 15.00 in
Height: 4.65 in
Weight: 10.3 kg

Adjustability

Free

Electric

System power: 122 W
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 66
IK: 08
Surface temperature: 40°C