# Product data sheet

LUCAS I (WALL FITTING BEADED) 9.835.2056.16

LEIPZIGER LEUCHTEN






CCT CRI



Mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets - Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

#### Light output 1



1 x High pressure sodium vap	oour lamp
Nominal lamp power	100 V
Lamp flux	10400 ln
Luminous efficacy	75 lm/V


 0400 lm
 ULOR
 2%

 25 lm/W
 Total flux
 8621 lm

 2000 K
 Total power
 115 W

83%

LOR



#### 1 x High pressure sodium vapour lamp

Nominal lamp power	70 W	LOR	83%
Lamp flux	5600 lm	ULOR	2%
Luminous efficacy	56 lm/W	Total flux	4642 lm
CCT	2000 K	Total power	83 W
CBI	25		

#### Mounting mode

Wall mounted

#### Shape and measurements

Height: 22.44 in Diameter: 22.44 in

#### Design

Material impression: Matt Color of housing: White

### Electric

System power: 83-115 W

Ballast: ECG Controller: DALI

# Integrated sensors

Integrated sensors: Motion sensor

#### Protection

IP: 55

Designation labels: CE

## Other operating numbers

Ambient temperature range: -4...95°F