


Product data sheet

LOUI BEAMLINE
921555.002.1
RZB




IP
20

IK
03


Series: LESS IS MORE BEAMLINE system Colour: traffic white, matt (RAL 9016) Length: 1121 mm Width: 71 mm Height: 1.5 mm Recess height: 125 mm Lamp: LED Socket: without socket Colour temperature: 4000K Colour rendering index (CRI): 90 System power: 48 W Rated luminous flux: 3900 lm Beam angle Down: 9° Luminous efficacy: 81 lm/W Control gear: Regulated power supply Protection class: I Type of protection: IP 20

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	24 W	CRI	90
Total flux	1950 lm	LOR	100%
Luminous efficacy	81 lm/W	ULOR	13%
		Total power	24 W

Light output 2 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	24 W	CRI	90
Total flux	1950 lm	LOR	100%
Luminous efficacy	81 lm/W	ULOR	13%
		Total power	24 W

Mounting mode

Ceiling recessed

Electric

System power: 48 W

Shape and measurements

Length: 2.80 in

Width: 44.13 in

Height: 0.08 in

Protection

IP: 20

IK: 03

Adjustability

Fixed

Design

Color of housing: White