Product data sheet


PARK LIGHTING
V1-S0-70GL6-54L75-6503040 GLIGHT 30W 4000K
VARTON



IP 66 IK 03

Glight is a stylish and reliable park luminaire designed for lighting streets, parks, boulevards, and pedestrian areas. With its durable aluminum housing, wide range of installation heights, and flexible control system, it is perfectly suited for modern urban environments. Input voltage (AC, 50Hz): 90...305 AC frequency: 50 Input voltage (DC): 127...300 Flicker: 3 Climatic modification and category of placement: УХЛ1 Protection class: I Ingress protection (IP): IP66 Impact resistance: IK03 Power factor: 0,95 https://www.varton.ru/products/parkovoe-osveshchenie/glight/glight_1/osvetitelnaya-sistema-varton-parkovyy-glight-60-vt-4000k-ral7045-seryy-8000-mm/

Light output 1



1 x LED

Nominal lamp power	30 W	LOR	100%
Lamp flux	4500 lm	Total flux	4501 lm
Luminous efficacy	150 lm/W	Total power	30 W
CCT	4000 K		
CRI	70		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 27.56 in
Width: 3.94 in
Height: 236.22 in

Adjustability

Fixed

Electric

System power: 30 W

Protection

IP: 66
IK: 03