

# Product data sheet

LANO 4 LED 40W 3000K M625 OPAL  
LITP0008-A  
SCHRACK TECHNIK




The Lano 4 recessed grid light is a high-quality luminaire designed for grid ceilings. It features an opal cover and provides efficient illumination, making it suitable for a variety of applications, especially in non-work areas and recreational spaces.

Performance and Efficiency: Power: 40W  
Luminous Flux: 4000lm Color Temperature: Available in 3000K or 4000K Color Rendering Index: CRI 90 for accurate color representation

Design: Suitable for M600, M625, M1200, and M1250 grid ceilings, featuring a sleek opal cover Driver: Not included; compatible with 1000mA drivers, available in On-Off or DALI versions Applications: Ideal for recreational areas and spaces where no work is performed

The Lano 4 recessed grid light combines high performance, excellent color rendering, and adaptability, making it an excellent choice for efficient and effective lighting in non-work areas and recreational spaces.

## Light output 1



1 x LED			
Nominal lamp power	39.76 W	LOR	100%
Lamp flux	4203 lm	ULOR	7%
Luminous efficacy	106 lm/W	Total flux	4202 lm
CCT	3000 K	Total power	39.76 W
CRI	90		

## Mounting mode

Ceiling recessed

## Shape and measurements

Length: 24.41 in  
Width: 24.41 in  
Height: 0.39 in

## Adjustability

Fixed

## Electric

System power: 39.76 W  
Appliance Class: III

## Protection

IP: 20  
Designation labels: CE

## Other operating numbers

Ambient temperature range: -4...86°F