



Product data sheet

X-LINE SLIM SURFACE LED 8800 MICRO-PRM EDD 04 830 / L-2258MM
19.4183.6113.04
LUXIONA



Indoor luminaire. Assembly: surface mounted on ceiling. The body material is aluminum. Colour - RAL 9005 (black). Luminaire dimensions: 2258 x 48 x 70 mm. Diffuser: Micro-PRM (micro-prismatic diffuser PMMA). The efficiency of the optical system is 74,32%. Beam angle: (C0-C180) / (C90-C270) - 88,4° / 86°. Light source type: LED. Colour of the light 3000 K. SDCM=3. CRI>80. Lifetime of LED sources: 100000 h L80/B10. Luminaire luminous flux: 6574,2 lm. Power of luminaire: 49,5 W. Luminaire's light efficiency: 132,6 lm/W. Driver: DIM DALI (EDD). Voltage 220..240 V, 50..60 Hz. Power factor cosφ: >0,95. Circuit load capacity: 14 (B10), 23 (B16), 22 (C10), 35 (C16). Operating temperature range: 5 ÷ 35° C. Protection degree: IP40. Impact resistant: IK04. Protection against electric shock: I. Photobiological risk class (IEC/EN 62471): RG0. The luminaire can be made in CLO (Constant Lumen Output) version.

Light output 1



1 x LED			
Nominal lamp power	49.5 W	LOR	83%
Lamp flux	8884 lm	Total flux	7415 lm
Luminous efficacy	179 lm/W	Total power	49.5 W
CCT	3000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 88.90 in

Width: 1.89 in

Height: 2.76 in

Adjustability

Fixed

Design

Color of housing: Black

Electric

System power: 49.5 W

Controller: DALI

Appliance Class: I

Protection

IP: 40

IK: 04

Other operating numbers

Ambient temperature range: 41...95°F