
Product data sheet

FUTURA 2.4FT CLASS II PCC 8800/840 DALI
47930
TREVOS



resistant to humidity and dust, with IP66 enclosure rating; optimal mounting height: 3.5 to 10 m; digitally dimmable DALI driver (AC/DC); Body: grey PC (high mechanical resistance, UV stability, RAL 7035); Diffuser: translucent PC (high mechanical resistance, UV stability); Reflector: steel sheet, white (RAL 9003); Clips: stainless steel + polyamide; Sealing: polyurethane (PUR), foam-filled base groove; Connection: screwless four-pole terminal block; Power: 52,8 W; Luminaire flux: 8440 lm; Lifetime: L90/B10; 50000 hours; Impact strength: IK10; Ambient temperature: -25|45 °C; Weight: 2,45 kg;

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	52.8 W	CRI	80
Total flux	8980 lm	LOR	100%
Luminous efficacy	170 lm/W	ULOR	4%
		Total power	52.8 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 46.14 in
Width: 5.71 in
Height: 4.41 in

Adjustability

Fixed

Design

Material impression: Plastic
Color of housing: Silver gray, White
Designer: TREVOS

Electric

System power: 52.8 W
Ballast: ECG
Controller: DALI
Appliance Class: II

Protection

IP: 66
IK: 10
Designation labels: CE, ENEC

Other operating numbers

Ambient temperature range: -13...113°F