

# Product data sheet

POZZO SCALE OPAL CEILING D500 830  
56130-402  
FAGERHULT



Installation Three securing holes surface mounting on the ceiling. Connection For fixed connection with 230 V, built-in LED ballast in luminaire. Terminal strip 5 x 2.5 mm². Possibility of 1-phase through-wiring. Possibility of external wire, 180 through pressure openings in the rear. Quick connection between mounting part and luminaire unit. Design Metal housing with white (RAL 9016) structured finish. Louvre Opal – plate in opal acrylic (PMMA). Delta – microprism louvre in acrylic (PMMA.). Dimming DALI/Phase-pulse control as standard. e-Sense Move – microwave sensors with lux threshold. Presence control high/low/off. All luminaires have master/slave functionality with RF communications.

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	18 W	CRI	80
Total flux	2321 lm	LOR	100%
Luminous efficacy	129 lm/W	Total power	18 W

## Mounting mode

Ceiling mounted

## Electric

System power: 18 W

## Shape and measurements

Length: 19.88 in

Width: 19.88 in

Height: 2.56 in

## Protection

IP: 40

## Adjustability

Fixed

## Design

Color of housing: White