


Product data sheet

PLACE BLACK 2410LM 3000K RA>80 ON/OFF
5703821172080
SG ARMATUREN



Design: Christian Hvidt. Mast or wall-mounted (600 mm diameter) IP66 LED luminaire. Base and top made of die-cast aluminium, inner diffuser made of PMMA opal and outer optics made of polycarbonate (PC). Grey or black base and top. Complete with LED driver for operation of LED light sources mounted to component rail with internal connector/lampholder and pre-mounted with five-metre connection cable. Prepared for mounting on 60 mm or designer mast. Safety class II. Light distribution Direct Light technic LED 21W 3000K Ra>80 SDCM3 L90/B10 >50,000 hrs L70/B10 >100,000 hrs Control/Dimming On/Off Protection Class II IP66 IK10 Materials and finish Housing: Die-cast aluminium Colour: Black (20% gloss) Optics: Polycarbonat (PC) Mounting/Connection Post - top (Ø60mm), Outdoor Cable 2x1mm² 6m Wind projected area: 0,0775m² - Max 10 kg Max. luminaires per circuit breaker: B10: 32, B16: 50, C10: 52, C16: 85

Light output 1



1 x LED			
Nominal lamp power	21 W	LOR	100%
Lamp flux	2410 lm	ULOR	21%
Luminous efficacy	115 lm/W	Total flux	2411 lm
CCT	3000 K	Total power	21 W
CRI	80		

Mounting mode

Pole top mounted

Shape and measurements

Length: 23.62 in

Width: 23.62 in

Height: 11.33 in

Adjustability

Fixed

Electric

System power: 21 W

Appliance Class: II

Protection

IP: 66

IK: 10