
Product data sheet

M20/M26H - SPY 391 93040 MDL
23315 9330
DELTA LIGHT




Luminaire, low voltage systems low voltage system mounted (indoor use) from Deltalight, named M20/M26H - SPY 391 93040 MDL, available in the colour(s): black, brushed alu, brushed anthracite, brushed copper, brushed gold, brushed old bronze, flemish bronze, flemish gold, gold coloured, piano black, white. This luminaire can be used with the following 48V magnetic lighting system(s): SHIFTLINE M26H - PROFILE, SLM26H F, SPLITLINE M20 - PROFILE, SPLITLINE M20 ST - PROFILE. This luminaire is equipped with LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1089lm with build-in converter to operate on a voltage of 48V-DC. Dimming protocol: MDL = 1-10V or DALI or push button. Light distributor: reflector 40°.

Light output 1




1 x LED

Nominal lamp power	9 W	LOR	73%
Lamp flux	1089 lm	Total flux	792 lm
Luminous efficacy	121 lm/W	Total power	20 W
CCT	3000 K		
CRI	90		




1 x LED

Nominal lamp power	9 W	LOR	73%
Lamp flux	1089 lm	Total flux	792 lm
Luminous efficacy	121 lm/W	Total power	20 W
CCT	3000 K		
CRI	90		



1 x LED

Nominal lamp power	9 W	LOR	73%
Lamp flux	1089 lm	Total flux	792 lm
Luminous efficacy	121 lm/W	Total power	20 W
CCT	3000 K		
CRI	90		



1 x LED

Nominal lamp power	9 W	LOR	73%
Lamp flux	1089 lm	Total flux	792 lm
Luminous efficacy	121 lm/W	Total power	20 W
CCT	3000 K		
CRI	90		

Mounting mode

Ceiling mounted, Contact rail, Floor mounted, Pendant, Standing / Bollard, Floor recessed

Shape and measurements

Length: 0.79 in
Width: 6.69 in
Height: 0.04 in

Electric

System power: 20 W
Appliance Class: II

Protection

IP: 20
Designation labels: CE