


Product data sheet

LINEDO_2,3M_OH_TW
95230H.803.476.010
RZB




IP
54


IK
04

LINEDO, 86. 90 W, 9000. 10100 lm, 827-865, black, DALI Continuous line luminaire, L 2291 B 58 H 91


Light output 1



1 x LED			
Nominal lamp power	21.5 W	LOR	100%
Lamp flux	2525 lm	Total flux	2525 lm
Luminous efficacy	117 lm/W	Total power	21.5 W
CCT	4600 K		
CRI	80		




1 x LED			
Nominal lamp power	22.5 W	LOR	100%
Lamp flux	2250 lm	Total flux	2250 lm
Luminous efficacy	100 lm/W	Total power	22.5 W
CCT	2700 K		
CRI	80		




1 x LED			
Nominal lamp power	22.5 W	LOR	100%
Lamp flux	2400 lm	Total flux	2400 lm
Luminous efficacy	107 lm/W	Total power	22.5 W
CCT	6500 K		
CRI	80		


Light output 2



1 x LED			
Nominal lamp power	22.5 W	LOR	100%
Lamp flux	2400 lm	Total flux	2400 lm
Luminous efficacy	107 lm/W	Total power	22.5 W
CCT	6500 K		
CRI	80		




1 x LED			
Nominal lamp power	21.5 W	LOR	100%
Lamp flux	2525 lm	Total flux	2525 lm
Luminous efficacy	117 lm/W	Total power	21.5 W
CCT	4600 K		
CRI	80		




1 x LED			
Nominal lamp power	22.5 W	LOR	100%
Lamp flux	2250 lm	Total flux	2250 lm
Luminous efficacy	100 lm/W	Total power	22.5 W
CCT	2700 K		
CRI	80		


Light output 3



1 x LED			
Nominal lamp power	22.5 W	LOR	100%
Lamp flux	2400 lm	Total flux	2400 lm
Luminous efficacy	107 lm/W	Total power	22.5 W
CCT	6500 K		
CRI	80		




1 x LED			
Nominal lamp power	21.5 W	LOR	100%
Lamp flux	2525 lm	Total flux	2525 lm
Luminous efficacy	117 lm/W	Total power	21.5 W
CCT	4600 K		
CRI	80		



1 x LED


Nominal lamp power	22.5 W	LOR	100%
Lamp flux	2250 lm	Total flux	2250 lm
Luminous efficacy	100 lm/W	Total power	22.5 W
CCT	2700 K		
CRI	80		

Light output 4




1 x LED

Nominal lamp power	22.5 W	LOR	100%
Lamp flux	2250 lm	Total flux	2250 lm
Luminous efficacy	100 lm/W	Total power	22.5 W
CCT	2700 K		
CRI	80		



1 x LED

Nominal lamp power	22.5 W	LOR	100%
Lamp flux	2400 lm	Total flux	2400 lm
Luminous efficacy	107 lm/W	Total power	22.5 W
CCT	6500 K		
CRI	80		



1 x LED

Nominal lamp power	21.5 W	LOR	100%
Lamp flux	2525 lm	Total flux	2525 lm
Luminous efficacy	117 lm/W	Total power	21.5 W
CCT	4600 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 2.28 in
Width: 90.20 in
Height: 3.58 in

Adjustability

Fixed

Electric

System power: 86-90 W

Protection

IP: 54
IK: 04