
Product data sheet

PANOS EVO Q68 10W LED827 VFL-WH WH
60815082
ZUMTOBEL



LED ceiling-recessed luminaire (Komplettleuchte), "Stable White"; maximum light quality thanks to specially designed reflector, lamp(s): 10 W LED827, VERY WIDEFLOOD distribution characteristic; reflector: smooth, white coated (75 °); Colour rendering Ra > 80, colour temperature 2700 K (warm white); Chromaticity tolerance (initial MacAdam): 3; Luminaire luminous flux: 640 lm, Luminaire efficacy: 64 lm/W; service life: 50000h at 85% luminous flux; includes control unit ; modular, high quality optical unit consisting of reflector and LED light chamber integrated in optimised thermal management of die-cast aluminium; reflector/trim made of high-quality, UV-resistant polycarbonate; white trim; mounting surround of die-cast aluminium; luminaire unit can be fitted quickly without tools using EASY-CLICK catch; IP20; luminaire wired with halogen-free leads; power connection: 2-pole terminal; mains voltage: 220-240V / 0/50/60Hz, for use with 220V DC central battery; tool-free quick installation using antislip spring clips in ceilings of thickness 1-25mm; ceiling cutout: 68x68 mm, recessed depth: 100mm; weight: 0.33 kg

Light output 1



1 x LED

Nominal lamp power	10 W	LOR	88%
Lamp flux	725 lm	Total flux	640 lm
Luminous efficacy	64 lm/W	Total power	10 W
CCT	3000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 3.07 in
Width: 3.07 in
Height: 3.03 in
Weight: 0.329 kg

Design

Material impression: Aluminum
Color of housing: White

Electric

System power: 10 W
Voltage: 220-240 V AC
Appliance Class: II

Protection

IP: 20
Designation labels: CE, ENEC