



Product data sheet

NANOTTICA 1.5FT ML PC 5500/840 3F
107304
TREVOS



absolute control over emitted light thanks to patented nano-optics; variable suspension spacing ranging from 970 - 1230 mm; enable the light to be installed onto suspension fittings left over from previous lighting; basic beam angle: medium beam (MB); optimal mounting height: 3.5 to 8 m; ON/OFF electronic driver (AC, DC on demand); Body: grey PC (high mechanical resistance, UV stability, RAL 7035); Diffuser: clear PC with nano-optics (high mechanical resistance, UV stability); Reflector: steel sheet, white (RAL 9003); Clips: polyamide + 15 % fibreglass; Sealing: polyurethane (PUR), foam-filled base groove; Connection: screwless five-pole terminal block, 5-wire connecting cabling for feed-through installation (1.5 mm2 cross-section, 2.5 mm2 available on demand); Power: 33,3 W; Luminaire flux: 5250 lm; Lifetime: L90/B10; 50000 hours; Impact strength: IK10; Ambient temperature: -25/45 °C; Weight: 2 kg;

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	33.3 W	CRI	80
Total flux	5590 lm	LOR	100%
Luminous efficacy	168 lm/W	ULOR	4%
		Total power	33.3 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 57.28 in
Width: 3.86 in
Height: 3.31 in

Adjustability

Fixed

Design

Material impression: Plastic
Color of housing: Silver gray, White
Designer: TREVOS

Electric

System power: 33.3 W
Ballast: ECG
Appliance Class: I

Protection

IP: 66
IK: 10
Designation labels: CE, ENEC

Other operating numbers

Ambient temperature range: -13...113°F