


# Product data sheet

RMT320 [S70] IP66:LED-12/24W/3K  
105-9893  
WE-EF



IP66. Class I. IK09. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. RFC® Reflection Free Contour main lens. Integral EC electronic converter, thermally separated. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. Factory installed LED circuit board. The luminaire is factory-sealed and does not need to be opened during installation. Recommended mounting height 3.0-5.0m, depending on wattage selected.

## Light output 1



|                    |          |             |         |
|--------------------|----------|-------------|---------|
| 12 x LED           |          |             |         |
| Nominal lamp power | 2 W      | LOR         | 87%     |
| Lamp flux          | 290 lm   | Total flux  | 3021 lm |
| Luminous efficacy  | 112 lm/W | Total power | 27 W    |
| CCT                | 3000 K   |             |         |
| CRI                | 80       |             |         |

## Mounting mode

Pole top mounted

## Shape and measurements

Height: 2.36 in  
Diameter: 19.69 in  
Weight: 8 kg

## Electric

System power: 27 W  
Appliance Class: I

## Protection

IP: 66  
IK: 09