Product data sheet


X-LINE SLIGHT L-DOWN LED 8800 PLX EDD 34 840 LINE-1S / L-2252MM S-1,5M
19.4421.C923.34
LUXIONA



IP 40 IK 04

Indoor luminaire. Assembly: surface mounted on slings. The body material is aluminum. Colour - RAL 9016 (white). Dimensions: 2252 x 34 x 68 mm. Diffuser: PLX (PMMA opal). The efficiency of the optical system is 75,50%. Beam angle: (C0-C180) / (C90-C270) - 99,6° / 103°. Light source type: LED. Colour of the light 4000 K. SDCM=3. CRI>80. Lifetime of LED sources: 80000 h L80/B10. Luminaire luminous flux: 7185 lm. Power of luminaire: 51,8 W. Luminaire's light efficiency: 138,7 lm/W. Driver: DIM DALI (EDD). Voltage 220..240 V, 50..60 Hz. Power factor cosφ: >0,95. Circuit load capacity: 14 (B10), 23 (B16), 22 (C10), 35 (C16). Operating temperature range: 5 ÷ 35° C. Protection degree: IP40. Impact resistant: IK04. Protection against electric shock: I. Photobiological risk class (IEC/EN 62471): RG0.

Light output 1



1 x LED

Nominal lamp power	51.8 W	LOR	52%
Lamp flux	9580 lm	Total flux	5023 lm
Luminous efficacy	185 lm/W	Total power	51.8 W
CCT	4000 K		
CRI	80		

Mounting mode

Pendant

Shape and measurements

Length: 88.66 in
Width: 1.34 in
Height: 2.68 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 51.8 W
Controller: DALI
Appliance Class: I

Protection

IP: 40
IK: 04

Other operating numbers

Ambient temperature range: 41...95°F