Product data sheet


GINO 1 SURFACE FACADE LUMINAIRES
GI-31631-W-T3-8040
LIGMAN



IP 65 IK 07


- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K and 4000K - Die-cast aluminium housing and frame - Pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Stainless steel fasteners in grade 304 with zinc flake coating (ZFC) - Durable silicone rubber gasket - Clear toughened glass - Integral control gear - Optional surface mounting box for easy wiring or conduit connection when wiring from behind is not possible

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	5 W	CRI	80
Total flux	378 lm	LOR	100%
Luminous efficacy	76 lm/W	ULOR	50%
		Total power	5 W

Light output 2 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	5 W	CRI	80
Total flux	472 lm	LOR	100%
Luminous efficacy	94 lm/W	ULOR	50%
		Total power	5 W

Mounting mode

Wall mounted

Shape and measurements

Length: 3.58 in
Width: 3.94 in
Height: 3.19 in
Weight: 0.87 kg

Adjustability

Fixed

Electric

System power: 10 W
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 65
IK: 07
Surface temperature: 40°C