Product data sheet


MIRAGE 3 165 SQUARE
WIDE BLACK
WHITECROFT



IP 44


See lamps to select output and colour variants MIRAGE 3 recessed square downlighter black reflector, wide distribution. Narrow 11mm width bezel and shallow depth body. Graphite heat sink for optimum thermal management and superior optics designed for maximum visual comfort. Simple spring ceiling retention method to suit ceiling thicknesses between 1-50mm. Supplied with connected remote driver. Large round, 165mm diameter cut out, 173mm over bezel. Anti ligature attachment kit 237mm diameter over bezel. Luminaire to be ordered separately Emergency Output:- 8w - 37% 16.6w - 19% 26.5w - 11% 35w - 9%

Light output 1




1 x LED

Nominal lamp power	8.4 W	LOR	100%
Lamp flux	619 lm	ULOR	13%
Luminous efficacy	74 lm/W	Total flux	619 lm
CCT	3000 K	Total power	8.4 W
CRI	80		




1 x LED

Nominal lamp power	35 W	LOR	100%
Lamp flux	2297 lm	ULOR	13%
Luminous efficacy	66 lm/W	Total flux	2297 lm
CCT	3000 K	Total power	35 W
CRI	80		




1 x LED

Nominal lamp power	26.5 W	LOR	100%
Lamp flux	1601 lm	ULOR	13%
Luminous efficacy	60 lm/W	Total flux	1601 lm
CCT	4000 K	Total power	26.5 W
CRI	90		




1 x LED

Nominal lamp power	26.5 W	LOR	100%
Lamp flux	1929 lm	ULOR	13%
Luminous efficacy	73 lm/W	Total flux	1929 lm
CCT	4000 K	Total power	26.5 W
CRI	80		




1 x LED

Nominal lamp power	26.5 W	LOR	100%
Lamp flux	1485 lm	ULOR	13%
Luminous efficacy	56 lm/W	Total flux	1485 lm
CCT	3000 K	Total power	26.5 W
CRI	90		




1 x LED

Nominal lamp power	35 W	LOR	100%
Lamp flux	2050 lm	ULOR	13%
Luminous efficacy	59 lm/W	Total flux	2050 lm
CCT	4000 K	Total power	35 W
CRI	90		




1 x LED

Nominal lamp power	26.5 W	LOR	100%
Lamp flux	1794 lm	ULOR	13%
Luminous efficacy	68 lm/W	Total flux	1794 lm
CCT	3000 K	Total power	26.5 W
CRI	80		




1 x LED

Nominal lamp power	16.6 W	LOR	100%
Lamp flux	1013 lm	ULOR	13%
Luminous efficacy	61 lm/W	Total flux	1013 lm
CCT	3000 K	Total power	16.6 W
CRI	90		




1 x LED

Nominal lamp power	16.6 W	LOR	100%
Lamp flux	1224 lm	ULOR	13%
Luminous efficacy	74 lm/W	Total flux	1224 lm
CCT	3000 K	Total power	16.6 W
CRI	80		




1 x LED

Nominal lamp power	8.4 W	LOR	100%
Lamp flux	552 lm	ULOR	13%
Luminous efficacy	66 lm/W	Total flux	552 lm
CCT	4000 K	Total power	8.4 W
CRI	90		




1 x LED

Nominal lamp power	8.4 W	LOR	100%
Lamp flux	666 lm	ULOR	13%
Luminous efficacy	79 lm/W	Total flux	666 lm
CCT	4000 K	Total power	8.4 W
CRI	80		




1 x LED

Nominal lamp power	8.4 W	LOR	100%
Lamp flux	512 lm	ULOR	13%
Luminous efficacy	61 lm/W	Total flux	512 lm
CCT	3000 K	Total power	8.4 W
CRI	90		




1 x LED

Nominal lamp power	16.6 W	LOR	100%
Lamp flux	1092 lm	ULOR	13%
Luminous efficacy	66 lm/W	Total flux	1092 lm
CCT	4000 K	Total power	16.6 W
CRI	90		




1 x LED

Nominal lamp power	16.6 W	LOR	100%
Lamp flux	1316 lm	ULOR	13%
Luminous efficacy	79 lm/W	Total flux	1316 lm
CCT	4000 K	Total power	16.6 W
CRI	80		



1 x LED

Nominal lamp power	35 W	LOR	100%
Lamp flux	2470 lm	ULOR	13%
Luminous efficacy	71 lm/W	Total flux	2470 lm
CCT	4000 K	Total power	35 W
CRI	80		



1 x LED

Nominal lamp power	35 W	LOR	100%
Lamp flux	1902 lm	ULOR	13%
Luminous efficacy	54 lm/W	Total flux	1902 lm
CCT	3000 K	Total power	35 W
CRI	90		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 6.69 in
Width: 6.69 in
Height: 3.94 in

Adjustability

Fixed

Electric

System power: 8.4-35 W

Protection

IP: 44