Product data sheet


LIGHTING FOR ADMINISTRATIVE AND OFFICE BUILDINGS
V1-R4-00010-31000-5403540 GR070/C 2.0 588X588X50 MM IP54 35W 4000K OPAL
VARTON



IP 54 IK 02

LED luminaire solution for GRILIATO ceilings with IP54. Stainless steel housing with white powder coating. Application: administrative facilities For GRILIATO suspended ceilings with special rails. Can be fixed at the level of GRILIATO cells with a height of 30, 40 or 50 mm. Length, mm: 588 Width, mm: 588 Height/depth, mm: 50 Input voltage (AC, 50Hz), V: 176...264 Power factor: 0,95 Ingress protection (IP): IP54 Impact resistance: IK02 Protection class: I AC frequency, Hz: 50 Flicker, %: 1 Climatic modification and category of placement: УХЛ4 https://www.varton.ru/products/ofisnoe-osveshchenie/varton-dlya-grilyato-gr-seriya-2-0/gr070-s-2-0-588kh588kh50-mm-ip54/svetodiodnyy-svetilnik-varton-gr070-c-2-0-588kh588kh50-mm-35-vt-4000-k-ip54-dlya-chistykh-pomeshchen/

Light output 1



1 x LED

Nominal lamp power	35 W	LOR	100%
Lamp flux	4200 lm	Total flux	4200 lm
Luminous efficacy	120 lm/W	Total power	35 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 23.15 in
Width: 23.15 in
Height: 1.97 in

Adjustability

Fixed

Electric

System power: 35 W

Protection

IP: 54
IK: 02