


Product data sheet

CIRCULAR OUTWARD Ø2000 SURFACE
CF4C-00X9AZDU05
LEDSC4



LedsC4 Circular Outward ø2000 Surface CF4C-00X9AZDU05V1 Pendant for indoor use. For sideways lighting. Structure finish: Black. Diffuser material: Polycarbonate. Diffuser finish: Opal. Warranty: 5 Years. Product net weight (Kg): 12 Product width or diameter (mm): 2042 Product height (mm): 5000 Class 1. IP: IP20. LED. No. of lampholders or LEDs: 1. Driver brand: MEAN WELL. Maximum power of light source: 123.2W. Colour temperature: 4000K. Colour rendering index: 90. MacAdam Steps: 3. Hours of life: 50.000h L80B20. UGR: 7.0. Photobiological risk: RG1. Real flux (lm): 10522. Real lm/W: 82. Voltage / frequency range: 90-305/50-60Hz. Voltage: 2,8. Equipment included: Yes. Total power: 129. Power factor: 0.90. Dimmable equipment included: DALI-2.

Light output 1



1 x LED			
Nominal lamp power	129 W	LOR	100%
Lamp flux	10522 lm	ULOR	49%
Luminous efficacy	82 lm/W	Total flux	10524 lm
CCT	4000 K	Total power	129 W
CRI	90		

Mounting mode

Pendant, Table luminaire

Shape and measurements

Length: 78.74 in
Width: 78.74 in
Height: 1.18 in

Adjustability

Fixed

Electric

System power: 129 W
Appliance Class: I

Protection

IP: 20